

# EasyPrint **mlp**<sup>X</sup> mini

## Multi-Lane Traversing Thermal Transfer Printer

The **EasyPrint MLP mini** is designed for versatility. The EasyPrint MLP is the ideal machine for in-line printing of batch codes, graphics, logos, sell-by dates, bar codes and other variable information. The thermal transfer technology prints directly onto packaging substrates such as poly films, foil, Tyvek®, medical paper, cartons and labels. The EasyPrint MLP provides solutions for multiple package coding and printing on Multivac, GEM, RapidPak, Repak, Ulma, Fargo Automation and all horizontal form, fill, seal, packaging machines.

### Multiple Lane Thermal Transfer Printing for:

- ✓ Pharmaceuticals
- ✓ Blister Packages
- ✓ Syringes
- ✓ Sutures
- ✓ Catheters
- ✓ Processed Meats
- ✓ Cheeses
- ✓ Pouches
- ✓ And more...



## EasyPrint **mlpX** mini



Mounted on a HFFS medical device packaging line



MLP on a VFFS



MLP printing on bottom web



Mounted on a HFFS food packaging line

## Benefits of EasyPrint Thermal Transfer Printing

### Saves Time and Money

Thermal transfer eliminates costly setup and downtime of changing metal or rubber type on hot stamp and competitive coders. No messy ink jet cleanup or downtime. The EasyPrint MLP is an easy alternative to labels and pre-printed films.

### More Prints Per Ribbon

Over 51,181 3/4 inch (19.05mm) prints per ribbon. The EasyPrint MLP has an automatic, highly accurate ribbon advance system that minimizes ribbon usage and delivers more prints per ribbon.

### High Speed

Unique electronic design enables printing at speeds up to 600mm/sec. across a web.



### EasyPrint MLP mini - Technical Specs

Technology	Direct Thermal Transfer	Time/Date	Yes
Print Area	Up to 8.3 x 23.62in (213 x 630mm)	Memory Storage	On Board USBx2, PCMCIA, or PC
Print Speed	From 25mm/sec up to 600mm/sec	Ribbon Length	3198 ft. (975m)
Print Density	300 DPI (12 dots/mm)	Communication	Serial RS 232, USB, Parallel DB25, Ethernet
# of lanes to print	Up to 99	Display	Color Touch Screen
Graphic Logos	BMP, DXF, PCX, TIF, WMF, GIF	Temperature	41°F-104°F (5°C-40°C)
Bar Codes	EAN 13, EAN 8, Code 39, 2/5 interleave, UPC A, UPC E, Code 128, EAN 128, HIBC LIC 128, PZN, EAN add-on, Date Code, Data Matrix	Humidity	10-80% without condensation
		Electrical	115/230 VAC, 50/60Hz, 400VA
		Compressed Air	.353 CFM@ 95 PSI, Max (10LT/min @ 6 Bar)



EasyPrint MLP mini VIDEO



EasyPrint MLP WAS VIDEO

Rev: 3.0